

PEEK KNOTLESS ANCHORS

- Designed for arthroscopic instability or rotator cuff repair.
- The knotless suture anchor uniquely allows surgeons to adjust tension on the tissue intraoperatively, ensuring precise tissue reduction and fixation.
- Knotless anchors are available in sizes: 2.9 mm, 3.5 mm, 4.5 mm, and 5.5 mm.
- The 2.9 mm and 3.5 mm Knotless anchors are optimized for labral repair.
- Use the 4.5 mm and 5.5 mm Knotless anchors for rotator cuff repair using the SutureBridge technique.
- The 3.5 mm Knotless anchor is used during rotator cuff or instability procedures.
- The anchor bodies are available in nonabsorbable PEEK materials.
- They are strong, revisable, and radiolucent implants with no MRI artifact.
- Each anchor has a PEEK eyelet for superior strength during insertion to allow firm tissue tensioning and shifting.



Order Informations

Ref Code 16655014 knotless anchor 5.5mm

Ref Code 16645014 knotless anchor 4.5mm

Ref Code 16635014 knotless anchor 3.5mm

Ref Code 16629014 knotless anchor 2.9mm

NeoSys

www.neosysmed.com



HAND
SLAP, BANKART
INSTABILITY



SHOULDER
TENDON AND
LIGAMENT REINSERTION



ANKLE
REINSERTION